# MPD ELECTROMAGNETIC CALORIMETER SIMULATION\*

## M.A. Martemianov, S.A. Bulychjov, V.V. Kulikov M.A. Matsyuk

NRC "Kurchatov Institute" — ITEP, Moscow 117218, Russia

YU.F. KRECHETOV, A.YU. SEMENOV, I.A. SEMENOVA, I.A. TYAPKIN

Joint Institute for Nuclear Research, Dubna, MR 141980, Russia

(Received February 1, 2021)

In the frame of the NICA/MPD project, a unique cylindrical electromagnetic calorimeter (ECal) is under construction. Recently, the design of the power frame was completed. This led to significant changes in the calorimeter structure. The report gives a brief description of the new ECal geometry and the modification of simulation procedure. As part of this program, independent module options have been developed to use in the test measurements on cosmic rays and electron beams.

DOI:10.5506/APhysPolBSupp.14.533

### 1. Introduction

A high priority for the Joint Institute for Nuclear Research (JINR) is a study of nuclear matter in a hot and dense state, including quark–gluon plasma [1]. To perform this task, a program to construct the NICA heavyions accelerator complex operating at high luminosity in the energy range of  $\sqrt{S} = 4$ –11 GeV and modern detectors was proposed. One such experimental setup, the Multi-Purpose Detector (MPD), is optimized to investigate the states of nuclear matter, which can occur through emission of the direct photons and dileptons [2]. Therefore, the realization of this purpose is impossible without the electromagnetic calorimeter (ECal) that was included in the first phase of the MPD assembly. Taking into account various factors such as high energy and time resolution, small Moliere radius, capability to operate in the magnetic field and low price allowed to select a

<sup>\*</sup> Presented at NICA Days 2019 and IV MPD Collaboration Meeting, Warsaw, Poland, October 21–25, 2019.

shashlik-type calorimeter [3]. The calorimeter cell (tower) of that type has a sampling structure consisting of active medium (scintillator) and absorber (lead). All towers form a barrel structure having a high segmentation as well as a projective geometry, which contains all calorimeter towers oriented to the NICA collider beams crossing area. The significant modifications of the MPD power supporting the frame proposed in the JINR design department led to important changes in the ECal structure and tower parameters. This paper describes the latest alterations in the geometry and resulting changes of physical parameters obtained from the MC simulation.

### 2. New ECal design

According to the new design concept, the power supporting frame is a barrel structure with an inner radius equal to 168 cm (Fig. 1, left). The inner radial wall of the power frame has a width of 2.5 cm. 25 bulkheads 1 cm thick provide high strength of the frame, which will be produced from lightweight carbon-fiber compound. 50 baskets will be placed inside the power frame. The baskets are required to accommodate the calorimeter modules and corresponding electronics. Each basket contains 48 modules: 8 modules of different shapes are arranged in a row along the Z-axis, 6 of the same shape — in XY-plane. The total weight of the basket is about 1.2 tons. Each module consists of 16 towers fixed by the special glue. The entire ECal has 38400 towers. Generally, each tower consists of 210 layers forming from 1.5 mm thick scintillator plate and 0.3 mm thick lead plate coated with reflective paint. The total length of the tower is 41.55 cm. or about 11 radiation length. The shapes of the towers are approximately truncated pyramids with a base of  $4 \times 4$  cm<sup>2</sup>, more accurately described by a set of trapezoids. Two milling angles equal to  $0.9^{\circ}$  along Z-axis and to  $1.2^{\circ}$ in XY-plane define 64 types of the tower shapes, which can be described by three spatial sizes a, b, c (Fig. 1, left). The behavior of these parameters



Fig. 1. Front view of the ECal and one calorimeter tower (left). Tower spatial sizes a, b, and c for different towers (right).

as a function of the tower number is shown in Fig. 1 (right). The towers are arranged to look at the beam intersection point determining the socalled projective geometry [4]. The location of the towers in the Z-plane is presented in Fig. 2 (left), where parameter  $\Delta Z$  defines the tower offset relative to the zero point. It is expected that the Gaussian smearing ( $\delta Z_{\rm IP}$ ) of the NICA collider interaction point is 24 cm, so the fluctuation of  $\Delta Z$ around zero does not exceed  $\delta Z_{\rm IP}$  (Fig. 2, right).



Fig. 2. Tower location in the Z-plane (left) and dependence of the parameter  $\Delta Z$  versus tower number.

#### 3. Calorimeter simulation with a simple clustering algorithm

The total ECal geometry is stored in ROOT file emc v3.root, where v3 is the current version number. In order to find the energy deposition in the tower, it is necessary to sum all Geant4 points in the active volume (scintillator). Its coordinates are defined as the center of tower, whose special location can be defined by two numbers: the number  $N_{\phi}$  in  $\phi$ -angle (from 0 to 299) and the number  $N_Z$  along the Z-axis (from 0 to 127) [5]. The cluster algorithm is based on the merging neighboring hits inside the grid  $N_{\phi} \times N_Z$  starting from the central hit with maximal energy deposition. The cluster energy is defined as a sum of hit energies, while the coordinate is calculated by the energy weighting sum of the coordinates of hit centers. The energy threshold of each hit was equal to 5 MeV. The following analysis of the ECal physical parameters was based on this cluster algorithm. The implementation of the various walls and edges as a part of the power frame leads to an enlargement of the reconstructed spectra and tails in the lowenergy region [5, 6]. Figure 3 (left) shows the energy of cluster from  $\gamma$ 's as a function of  $\theta$ -angle. Photons are well reconstructed in the  $\theta$ -angle region from 35° to 145°. The effective mass of two  $\gamma$ 's reconstructed from  $\pi^0$  decays at p = 200 MeV/c is shown in Fig. 3 (right). This distribution is given for two calculations. In the first case, the simulation was performed for full MPD geometry including the different detectors (TOF and TDC) and the

power frame (PF); in the other case, only calorimeter modules were taken into account. A significant distortion of the effective mass distribution by shape is seen; an essential tail at the low-energy range is clearly manifested in the first case.



Fig. 3. Cluster energy produced by single photon versus  $\theta$ -angle at  $E\gamma = 1$  GeV (left). Reconstructed  $\gamma\gamma$  effective mass from  $\pi^0$  decays at p = 200 MeV/c (right).

## 4. Conclusion

A new geometry program of the MPD electromagnetic calorimeter has been created and stored in the ROOT-file to be used in the MpdRoot software. It includes special supporting structures, calorimetric modules and a new description of the minimal calorimeter cell — tower. Corresponding physical distributions simulated for photons of the different energies have been shown.

This work was supported by the Russian Foundation of Basic Research (RFBR) grants No. 18-02-40054 and No. 18-02-40079.

#### REFERENCES

- [1] V.D. Kekelidze, *Phys. Part. Nucl.* **49**, 457 (2018).
- [2] V. Golovatyuk et al., Eur. Phys. J. A 52, 212 (2016).
- [3] G.S. Atoian et al., Nucl. Instrum. Methods Phys. Res. A 584, 291 (2008).
- [4] MPD NICA Technical Design Report of the Electromagnetic calorimeter, http://mpd.jinr.ru/wp-content/uploads/2017/09/TDR\_ECAL\_v1.3.pdf
- [5] B. Dabrowska et al., EPJ Web Conf. 204, 07015 (2019).
- [6] C. Shen et al., JINST 14, T06005 (2019).